



## Knowledge Based Systems

Jacek Malec

Dept. of Computer Science, Lund University, Sweden

February 11, 2016



## Programming vs KR

Programming:

- construct an algorithm to solve a problem
- choose a programming language
- implement the algorithm in the language
- run the program to solve the problem

Knowledge Representation and Engineering:

- identify knowledge necessary to solve the problem
- choose a representation language
- formulate knowledge in the language
- check if solution can be derived



## Knowledge

There is evidence that people memorize just **the important stuff**.

- objects
- facts, relations
- rules (generic knowledge)
- causality
- meta-knowledge
- procedural knowledge
- knowledge about processes
- ...



## Meta-knowledge

knowledge about other's (or our own)

- knowledge (Jacek knows that Earth revolves around Sun)
- beliefs (Jacek believes that his daughter is smart)
- needs (Jacek needs more time for checking assignments)
- goals (Jacek wants to write a paper by Friday)
- intentions (Jacek wants to be ready with checking Assignment 1 by next Thursday)
- capabilities (Jacek can drive)
- ...




## Procedural knowledge

How to:

- change a diaper?
- serve in tennis?
- ride a bicycle?
- drive a car?
- ...



## Ontology




## Problems with predicate logic:

- static
- flat
- qualification/ramification/frame problem
- exceptions
- strength
- ...




## Actions, situations







# Events



# Events



# Interval calculus



# Representation of exceptions:

$\forall x (Bird(x) \wedge \neg Pinguin(x) \wedge \neg Ostrich(x) \rightarrow Flies(x))$   
 But if we know  $Bird(Tweety)$  we can't say whether it flies!

Qualification Problem:

Unfortunately, many other birds don't fly either: caged birds, dead birds, birds with broken wing, bird with feathers covered by oil, ...  
 $\forall x (Bird(x) \wedge \neg Pinguin(x) \wedge \neg Ostrich(x) \wedge \dots \rightarrow Flies(x))$

Other related problems: frame problem, ramification problem



## Solutions:

- non-monotonic logics
- fuzzy logic
- probabilistic logic
- possibilistic logic
- ...



## Monotonic vs. non-monotonic

$Th(\Delta)$

monotonic logic:

if  $\Delta \subseteq \Delta'$  then  $Th(\Delta) \subseteq Th(\Delta')$

non-monotonic logic:

if  $\Delta \subseteq \Delta'$  and  $Th(\Delta) \supset Th(\Delta')$



## Closed World Assumption:

**Things that cannot be proven true are probably false**

leads to:

**Negation as failure**



## Consider:

$$\Delta = \{A(\text{Stockholm}), A(\text{Sturup}), A(\text{Copenhagen}), \\ A(\text{Oslo}), \text{Conn}(\text{Oslo}, \text{Copenhagen}), \\ \text{Conn}(\text{Stockholm}, \text{Oslo}), \\ \forall(x, y, z)(\text{Conn}(x, y) \wedge \text{Conn}(y, z) \rightarrow \text{Conn}(x, z))\}$$

Because it's not the case that  $\text{Conn}(\text{Sturup}, \text{Stockholm})$ , CWA gives us immediately  $\neg \text{Conn}(\text{Sturup}, \text{Stockholm})$ . But let us add  $\text{Conn}(\text{Sturup}, \text{Copenhagen})$  to  $\Delta$ .  $\text{Conn}(\text{Sturup}, \text{Stockholm})$  can be proven now, so  $\neg \text{Conn}(\text{Sturup}, \text{Stockholm})$  does not appear as a consequence. Non-monotonicity!



## CWA is syntax-dependent:

If  $\Delta = \{Single(John), Single(Mary), Clever(Kent)\}$   
 then CWA gives us:  
 $\{\neg Clever(John), \neg Clever(Mary), \neg Single(Kent)\}$ .

But if  $\Delta = \{\neg Married(John), \neg Married(Mary), Clever(Kent)\}$   
 then CWA gives us:  
 $\{\neg Clever(John), \neg Clever(Mary), \neg Married(Kent)\}$ .



## Effective representation of knowledge:

- storing
- retrieval
- modification

What should be represented?

- use logic
- not necessarily FOL


How should it be represented?

- whatever method you find suitable



## Semantic networks:

Precursor of Description Logics and Semantic Web Languages  
 (OWL, DAML, OIL, ...)



## Reasoning in SN:

- inheritance via SubsetOf (SubClass) and MemberOf (isA) links
- intersection paths
- special meaning associated with some links (like cardinality constraints, etc.)
- classification, consistency, subsumption

May be effective given some restrictions on the logic (DL variants).  
 Rule-based reasoning on top (RIF and co.)



## Knowledge-Based Systems

A generic term, might denote anything that involves encoded knowledge.

Or might mean a system where the knowledge component is *explicit* and manipulable.

Paradigms throughout history of AI:

- Logic-based systems;
- Rule-based systems (expert systems);
- Blackboard systems;
- Semantic web systems.



## Rule-based systems

Or *expert systems*.

Promised much. Delivered (too) little. Caused “AI Winter” in the 90s.

Simple architecture:

- Facts;
- Rules;
- Inference engine:
  - Matching;
  - Conflict resolution;
  - Rule application.




## Blackboard systems

Architecture:

- Knowledge base (blackboard);
- Knowledge sources (expert problem solvers);
- Controller (agenda maintainer).




## A blackboard system





## Semantic Web



Linking Open Data cloud diagram, by Richard Cyganiak and Anja Jentzsch. <http://lod-cloud.net/>



## Semantic Web

Lots of hype. Lots of acronyms. But some are important!

- URI – Uniform Resource Identifier
- RDF – Resource Description Framework
- RIF – Rule Interchange Format
- SPARQL – SPARQL Protocol and RDF Query Language
- OWL – Web Ontology Language

Open World Assumption!



## SPARQL

W3C Recommendation

Queries:

- SELECT (returns a table)
- CONSTRUCT (returns RDF)
- ASK (returns a boolean)
- DESCRIBE (freedom)

Example:

```
PREFIX foaf: <http://xmlns.com/foaf/0.1/>
SELECT ?name ?email
WHERE {
  ?person a foaf:Person.
  ?person foaf:name ?name.
  ?person foaf:mbox ?email.
}
```



## A SPARQL query

What are all the country capitals in Africa?

```
PREFIX abc: <http://example.com/exampleOntology#>
SELECT ?capital ?country
WHERE {
  ?x abc:cityname ?capital ;
    abc:isCapitalOf ?y .
  ?y abc:countryname ?country ;
    abc:isInContinent abc:Africa .
}
```



## A real SPARQL query

```


http://wiki.dbpedia.org/OnlineAccess
http://kif.cs.lth.se

select ?s where {
  ?s a rosetta:Camera.
}


select distinct ?s ?v where {
  ?s a rosetta:Camera.
  ?s ?p ?n.
  ?n caex-xml:hasName "FocusRange".
  ?n caex-xml:hasValue ?v.
}
    
```




## A real case



## A real case




## A real case







# A real case




# A real case



# A real case




# A real case






## A real case



## A real case



## Next period: EDAN70

### EDAN70 Project in Computer Science (AKA Intelligent Systems)

- topics proposed by us (PN, EAT, JM)
- but: you may choose your own
- personal supervision
- research-related problems
- workload: normal course, 7.5 hp
- First meeting after Easter, 31/3, 15.15 in E:2116
- but: contact us earlier if you are interested