

EDAF30 – Programming in C++

*5. Functions. The standard library.*

Sven Gestegård Robertz  
*Computer Science, LTH*

2020



# Outline

- 1 Standard library algorithms
  - Algorithms
  - Insert iterators
- 2 Iterators
  - Different kinds of iterators
  - stream iterators
- 3 Algorithms and function objects

# Algorithms

## Standard library algorithms

```
#include <algorithm>
```

## Numeric algorithms:

```
#include <numeric>
```

## Random number generation

```
#include <random>
```

Appendix A.2 in Lippman gives an overview

## Main categories of algorithms

- 1 Search, count
- 2 Compare, iterate
- 3 Generate new data
- 4 Copying and moving elements
- 5 Changing and reordering elements
- 6 Sorting
- 7 Operations on sorted sequences
- 8 Operations on sets
- 9 Numeric algorithms

## Algorithm limitations

- ▶ Algorithms may *modify container elements*. E.g.,
  - ▶ `std::sort`
  - ▶ `std::replace`
  - ▶ `std::copy`
  - ▶ `std::remove` (sic!)
- ▶ No algorithm *inserts or removes container elements*.
  - ▶ That requires operating on the actual container object
  - ▶ or using an *insert iterator* that knows about the container (cf. `std::back_inserter`)

# Algorithms

## Exempel: find

```
template <class InputIterator, class T>
InputIterator find (InputIterator first, InputIterator last,
                  const T& val);
```

### Exempel:

```
vector<std::string> s{"Kalle", "Pelle", "Lisa", "Kim"};

auto it = std::find(s.begin(), s.end(), "Pelle");

if(it != s.end())
    cout << "Found " << *it << endl;
else
    cout << "Not found"<< endl;
```

Found Pelle

# Algorithms

## Example: find\_if

```
template <class InputIterator, class UnaryPredicate>
InputIterator find_if (InputIterator first, InputIterator last,
                     UnaryPredicate pred);
```

### Exempel:

```
bool is_odd(int i) { return i % 2 == 1; }

void test_find_if()
{
    vector<int> v{2,4,6,5,3};

    auto it = std::find_if(v.begin(), v.end(), is_odd);

    if(it != v.end())
        cout << "Found " << *it << endl;
    else
        cout << "Not found"<< endl;
}
```

Found 5

*Function pointer*

Count elements, in a data structure, that satisfy some predicate

- ▶ `std::count(first, last, value)`
  - ▶ elements equal to value
- ▶ `std::count_if(first, last, predicate)`
  - ▶ elements for which predicate is true



# Algorithms

## Example: copy and copy\_if

```
template <class InputIterator, class OutputIterator>
OutputIterator copy (InputIterator first, InputIterator last,
                    OutputIterator result);
```

### Example:

```
vector<int> a(8,1);

print_seq(a);           length = 8: [1][1][1][1][1][1][1][1]

vector<int> b{5,4,3,2};

std::copy(b.begin(), b.end(), a.begin()+2);
print_seq(a);           length = 8: [1][1][5][4][3][2][1][1]
```

*copy\_if with predicate, as previous slide*

Remove elements equal to a value or matching a predicate.

- ▶ `std::remove` et al. do not actually remove anything. They
  - ▶ move the “retained” elements to the front
  - ▶ return an iterator to the first “removed” element
- ▶ To actually remove from a container, use the `erase` member function, e.g `std::vector::erase()`

### The erase-remove idiom

```
auto new_end = std::remove_if(c.begin(), c.end(), pred);  
c.erase(new_end, c.end());
```

or

```
c.erase(std::remove_if(c.begin(), c.end(), pred), c.end());
```

# Algorithms

## Insert iterators (in <iterator>)

### Example:

```
vector<int> v{1, 2, 3, 4};
```

```
vector<int> e;  
std::copy(v.begin(), v.end(), std::back_inserter(e));  
print_seq(e);  
length = 4: [1][2][3][4]
```

```
deque<int> e2;  
std::copy(v.begin(), v.end(), std::front_inserter(e2));  
print_seq(e2);  
length = 4: [4][3][2][1]
```

```
std::copy(v.begin(), v.end(), std::inserter(e2, e2.end()));  
print_seq(e2);  
length = 8: [4][3][2][1][1][2][3][4]
```

# Requirements on iterators

The standard library algorithms put requirements on iterators.  
For instance, `std::find` requires its arguments to be

`CopyConstructible` (and `Destructible`) as it is passed by value

`EqualityComparable` to have `operator!=`

`Dereferencable` to have `operator*` (for reading)

`Incrementable` to have `operator++`

The requirements are often specified using iterator concepts.

# Iterator concepts

- ▶ Input Iterator (++, ==, !=) (dereference as *rvalue*: \*a, a->)
- ▶ Output Iterator (++) (dereference as *lvalue*: \*a=t)
- ▶ Forward Iterator (Input- and Output Iterator, reusable)
- ▶ Bidirectional Iterator (as Forward Iterator with --)
- ▶ Random-access Iterator (+=, -=, a[n], <, <=, >, >=)

Different iterators for a container type (con is one of the containers `vektor`, `deque`, or `list` with the element type `T`)

<code>con&lt;T&gt;::iterator</code>	runs forward
<code>con&lt;T&gt;::const_iterator</code>	runs forward, only for reading
<code>con&lt;T&gt;::reverse_iterator</code>	runs backwards
<code>con&lt;T&gt;::const_reverse_iterator</code>	runs backwards, only for reading

# Iterator validity

In general, if the structure an iterator is referring to is changed *the iterator is invalidated*. Example:

- ▶ insertion
  - ▶ sequences
    - ▶ vector, deque\* : all iterators are invalidated
    - ▶ list : iterators are unaffected
  - ▶ associative containers (set, map)
    - ▶ iterators are unaffected
- ▶ removal
  - ▶ sequences
    - ▶ vector : iterators *after* the removed elements are invalidated
    - ▶ deque : all iterators invalidated (in principle\*)
    - ▶ list : iterators to the removed elements are invalidated
  - ▶ associative containers (set, map)
    - ▶ iterators are unaffected
- ▶ resize: as insertion/removal

## istream\_iterator<T> : constructors

```
istream_iterator(); // gives an end-of-stream istream iterator  
istream_iterator (istream_type& s);
```

```
#include <iterator>
```

```
stringstream ss{"1 2 12 123 1234\n17\n\t42"};
```

```
istream_iterator<int> iit(ss);
```

```
istream_iterator<int> iit_end;
```

```
while(iit != iit_end) {  
    cout << *iit++ << endl;
```

```
}
```

```
1
```

```
2
```

```
12
```

```
123
```

```
1234
```

```
17
```

```
42
```

Example: use to initialize a vector<int>:

```
stringstream ss{"1 2 12 123 1234\n17\n\r42"};

istream_iterator<int> iit(ss);
istream_iterator<int> iit_end;

vector<int> v(iit, iit_end);

for(auto a : v) {
    cout << a << " ";
}
cout << endl;
```

1 2 12 123 1234 17 42



Example: counting words in a string s:

## Straight-forward counting

```
istringstream ss{s};  
int words{0};  
string tmp;  
while(ss >> tmp) ++words;
```

## Using the standard library

```
istringstream ss{s};  
int words = distance(istream_iterator<string>{ss},  
                    istream_iterator<string>{});
```

`std::distance` gives the distance (in number of elements) between two iterators. (UB if the second argument cannot be reached by incrementing the first.)

## istream\_iterator

### Handling errors

```
stringstream ss2{"1 17 kalle 2 nisse 3 pelle\n"};
istream_iterator<int> iit2{ss2};
istream_iterator<int> iit_end;
while(!ss2.eof()) {
    while(iit2 != iit_end) { cout << *iit2++ << endl; }
    if(ss2.fail()){
        ss2.clear();
        string s;
        ss2 >> s;
        cout << "ss2: not an int: " << s << endl;
        iit2 = istream_iterator<int>(ss2); // create new iterator
    }
}
```

```
cout << boolalpha << "ss2.eof(): " << ss2.eof() << endl;
```

```
1
17
ss2: not an int: kalle
2
ss2: not an int: nisse
3
ss2: not an int: pelle
ss2.eof(): true
```

- ▶ on failure, the fail-bit is set in the stream
- ▶ the iterator is set to end
- ▶ if the stream is changed, a new iterator must be created

## ostream\_iterator

```
ostream_iterator (ostream_type& s);  
ostream_iterator (ostream_type& s, const char_type* delimiter);
```

```
std::vector<int> v{1,2,12,1234,17,42};  
cout << fixed << setprecision(2);  
ostream_iterator<double> oit{cout, " <-> "};
```

```
std::copy(begin(v), end(v), oit);
```

```
1.00 <-> 2.00 <-> 12.00 <-> 1234.00 <-> 17.00 <-> 42.00 <->
```

Iterate over a sequence, apply a function to each element and write the result to a sequence (cf. “*map*” in functional programming languages)

```
template < class InputIt, class OutputIt, class UnaryOperation >
OutputIt transform( InputIt first, InputIt last, OutputIt d_first,
                   UnaryOperation unary_op );
```

```
template < class InputIt1, class InputIt2, class OutputIt,
           class BinaryOperation >
OutputIt transform( InputIt1 first1, InputIt1 last1, InputIt2 first2,
                   OutputIt d_first, BinaryOperation binary_op );
```

A function object is an object that can be called as a function.,

- ▶ function pointers
- ▶ function objects (“*functor*”)

The algorithm transform can handle both function pointers and functors.

## Example with function pointer

```
int square(int x) {
    return x*x;
}

vector<int> v{1, 2, 3, 5, 8};
vector<int> w; // w is empty!

transform(v.begin(), v.end(), inserter(w, w.begin()), square);

// w = {1, 4, 9, 25, 64}
```

# Function objects

A function object is an object that has `operator()`

## Previous example with a function object

```
struct {  
    int operator() (int x) const {  
        return x*x;  
    }  
} sq;  
  
vector<int> v{1, 2, 3, 5, 8};  
vector<int> ww; // ww empty!  
  
transform(v.begin(), v.end(), inserter(ww, ww.begin()), sq);  
  
// ww = {1, 4, 9, 25, 64}
```

*Anonymous struct* – *the type* has no name, only *the object*.

# Function objects

## functions with state

Function objects can be used to create functions with state (more flexible than static local variables).

### Example

```
struct {
    int operator()(int x) {return val+=x;}
    int get_sum() const {return val;}
    void reset() {val=0;}
    int val=0;
} accum;

std::vector<int> v{1,2,3,4,5};

for(auto x : v) {
    cout << "sum is " << accum(x) << endl;
}
cout << "Total sum is " << accum.get_sum() << endl;
```

# Random numbers

<cstdlib>

## Example: dice with the C standard lib

```
#include <iostream>
#include <cstdlib>
#include <ctime>

using std::cout;
using std::endl;

int main( )
{
    unsigned int seed = time(0);
    srand(seed);

    for (int i=0; i<20; ++i) {
        cout << rand()%6+1 << " ";
    }
    cout << endl;
}
```



# Random numbers

Better C++: encapsulate in an object – “function with state”

Assume that we have a class `Rand_int` giving random numbers in the interval  $[min, max]$ .

## with RandInt object

```
int main()
{
    unsigned long seed = time(0);
    Rand_int die(1, 6, seed);

    for(int i = 0; i < 20; ++i) {
        cout << die() << " ";
    }
    cout << endl;
}
```

## The C version

```
int main( )
{
    unsigned int seed = time(0);
    srand(seed);

    for (int i=0; i<20; i++) {
        cout << rand()%6+1 << " ";
    }
    cout << endl;
}
```

# Random numbers

## Example of a random integer class

### Example: Rand\_int

```
#include <random>

class Rand_int {
public:
    Rand_int(int low, int high) :dist{low,high} {}
    Rand_int(int low, int high, unsigned long seed)
        :re{seed}, dist{low,high} {}
    int operator()() {return dist(re);}
private:
    std::default_random_engine re;
    std::uniform_int_distribution<> dist;
};
```

# Function objects

## lambda expressions

### syntax:

```
[capture] (parameters) -> return type {statements}
```

### where

**capture** specifies by value (`[=]`) or by reference (`[&]`), default or for each named variable (e.g., `[&x, y]`)

**parameters** are like normal function parameter declaration

**return type** can be inferred from **return** statements if unambiguous

### Example

```
auto plus = [](int a, int b) {return a + b;}  
  
int x = 10;  
auto plus_x = [=](int a) {return a + x;} // x is captured
```

# Function objects

Predefined function objects: `<functional>`

## Functions:

`plus`, `minus`, `multiplies`, `divides`, `modulus`, `negate`,  
`equal_to`, `not_equal_to`, `greater`, `less`, `greater_equal`,  
`less_equal`, `logical_and`, `logical_or`, `logical_not`

## Predefined function object creation

`operation<type>()`

E.g.,

```
auto f = std::plus<int>();
```

# Function objects

Example: `std::plus` from `<functional>`

## transform with binary function

```
vector<int> v1{1,2,3,4,5};  
vector<int> v2(10,10);  
  
vector<int> res2;  
auto it = std::back_inserter(res2);  
auto f = std::plus<int>();  
std::transform(v1.begin(), v1.end(), v2.begin(), it, f);  
  
print_seq(res2);  
  
length = 5: [11][12][13][14][15]
```

## Example with `accumulate` `<numeric>`

```
auto mul = std::multiplies<int>();  
int prod = std::accumulate(v1.begin(), v1.end(), 1, mul);  
  
cout << "product(v1) = " << prod << endl;  
  
product(v1) = 120
```

# Function objects

## Example: a function object class template

```
template<typename T>
class Less_than {
    const T val;
public:
    Less_than(const T& v) :val{v} {}
    bool operator()(const T& x) {return x < val;}
};

void use_less_than()
    Less_than<int> lt5{5};
    std::vector<int> v{1, 7, 6, 2, 8, 4, 9, 3};
    std::vector<int> small;

    std::copy_if(begin(v), end(v), std::back_inserter(small), lt5);

    for (auto x : small) {
        cout << x << " ";
    }
    cout << endl;
}
```

# Custom comparator for `std::set`

A `std::set<T>` is sorted

- ▶ using `operator<` by default
- ▶ or with a custom binary predicate

The predicate should be of the form `bool (const T&, const T&)`, and can be given as

- ▶ a function pointer
- ▶ a functor
  - ▶ an object of a class with `operator()(const T&, const T&)`
  - ▶ the value of a lambda expression

## The type parameters

```
template< class Key,  
          class Compare    = std::less<Key>,  
          class Allocator  = std::allocator<Key>  
> class set;
```

## And some constructors:

```
set();
```

```
explicit set( const Compare& comp,  
              const Allocator& alloc = Allocator() );
```

```
set( std::initializer_list<value_type> init,  
     const Compare& comp = Compare(),  
     const Allocator& alloc = Allocator() )
```



# Custom comparator for `std::set`

```
struct Longest_Str{
    bool operator()(const string& l, const string &r) const {
        return l.size() > r.size();}
};

bool short_str(const string& l, const string& r)
{
    return l.size() < r.size();
}
```

```
#include <set>

std::set<string, Longest_Str> s{"a", "bb"};
std::set<string, Longest_Str> s2;

using StrComp = bool (*)(const string&, const string&);
std::set<string, StrComp> t({"x", "yy"}, short_str);
std::set<string, StrComp> t2(short_str);
```

# Suggested reading

References to sections in Lippman

Function templates 16.1.1

Algorithms 10 – 10.3.1, 10.5

Iterators 10.4

Function objects 14.8

Random numbers 17.4.1

## Resource management

References to sections in Lippman

Dynamic memory and smart pointers 12.1

Dynamically allocated arrays 12.2.1

Classes, resource management 13.1, 13.2