

# EDAF50 – C++ Programming

## 7. *Generic programming*

Sven Gestegård Robertz  
*Computer Science, LTH*

2022



# Outline

## 1 Function templates

- Template arguments
- Function objects

## 2 Class templates

- Class templates

# Function templates

## Example: compare

```
template<class T>
int compare(const T& a, const T& b) {
    if (a < b) return -1;
    if (b < a) return 1;
    return 0;
}
```

Can be instantiated for all types that have an **operator<**

# Function templates

## Requirements on types

### Example: another compare template

```
template<class T>
int compare(T a, T b) {
    if (a < b) return -1;
    if (a == b) return 0;
    return 1;
}
```

More requirements on the type T:

- ▶ call-by-value: T must be copy constructible
- ▶ needs both **operator<** and **operator==**

*Try to minimize the requirements on T*

# Templates Concepts

- ▶ A concept is a named set of requirements (on a type)
- ▶ for template arguments
- ▶ Not yet part of the C++ language

Some example concepts

**DefaultConstructible** Objects can be constructed without explicit initialization

**CopyConstructible, CopyAssignable** Objects (of type X) can be copied and assigned.

**LessThanComparable**  $a < b$  is defined

**EqualityComparable**  $a == b$  and  $a != b$  is defined

**Iterator** and the more specific **InputIterator**, **OutputIterator**, **ForwardIterator**, **RandomAccessIterator**, etc.

# Function templates

Example: type deduction

```
template <typename T>
int compare(const T& a, const T& b)
{
    if(a < b) return -1;
    if(b < a) return 1;
    return 0;
}

void example()
{
    int x{4};
    int y{2};
    cout << "compare(x,y): " << compare(x,y) << endl;      T is int

    string s{"Hello"};
    string t{"World"};
    cout << "compare(s,t): " << compare(s,t) << endl;      T is string
}
```

*The compiler can (often) infer the template parameters from the function arguments.*

# Function templates

## Parameters must match

```
template <typename T>
int compare(const T& a, const T& b);
```

### Example: compare

```
int i{5};
double d{5.5};

cout << compare(i,d) << endl;
```

error: no matching function for call to 'compare(int&, double&)'  
▶ First argument gives: T is **int**  
▶ Second argument gives: T is **double**  
▶ Template is not instantiated (not an error)  
▶ There is no function compare(**int, double**) (error)

*Types must match exactly. No implicit conversions are performed.*

# Templates

## Template instantiation: SFINAE

### Substitution Failure Is Not An Error

If a template instantiation produces ill-formed code

- ▶ it is considered not viable
- ▶ and is silently discarded.

If *no viable instantiation* is found it is an error  
("no such class/function")

# Function templates

## Explicit instantiation

```
template <typename T>
int compare(const T& a, const T& b);
```

### Example: compare with explicit instantiation

```
int i{5};
double d{5.5};

cout << compare<double>(i,d) << endl;      // -1
cout << compare<int>(i,d) << endl;           // 0
```

*An explicitly instantiated function template is just a function.  
⇒ implicit type conversion of arguments*

# Function templates

Prefer type casts to be clear about type conversions

```
template <typename T>
int compare(const T& a, const T& b);
```

Example: compare with explicit type conversion

```
int i{5};
double d{5.5};

cout << compare(static_cast<double>(i),d) << endl; // -1
cout << compare(i,static_cast<int>(d)) << endl;      // 0
```

*For readability, it is often better to be explicit about type conversions than to rely on implicit type conversion of arguments*

# Function templates

## Example: two template parameters

```
template <typename T, typename U>
int compare2(const T& a, const U& b)
{
    if(a < b) return -1;
    if(b < a) return 1;
    return 0;
}

void example3()
{
    int i{5};
    double d{5.5};

    cout << compare2(i,d) << endl; // -1
}
```

- ▶ First argument gives: T is **int**
- ▶ Second argument gives: U is **double**      *OK!*

# Function templates

## Example: the minimum function

```
template<class T>
const T& minimum(const T& a, const T& b) {
    if (a < b)
        return a;
    else
        return b;
}
```

Can be instantiated for all types that have the operator <

# Function templates

## Overloading with a normal function

```
struct Name{  
    string s;  
    //...  
};
```

### Overload for Name&

```
const Name& minimum(const Name& a, const Name& b)  
{  
    if(a.s < b.s)  
        return a;  
    else  
        return b;  
}
```

# Function templates

## Trailing return type (c++11)

```
template <typename T, typename U>
T minimum(const T& a, const U& b);
```

Would not always work, as the return type is always that of the first argument.

```
template <typename T, typename U>
auto minimum(const T& a, const U& b) -> decltype(a+b)
{
    return (a < b) ? a : b;
}                                ▶ decltype is an unevaluated context
void example()                  ▶ the expression a + b is not evaluated
{
    int a{3};                   ▶ decltype gives the type of an expression
    int b{4};
    double x{3.14};            ▶ NB! Return-by-value as argument may
                               need to be converted

    cout << "minimum(x,a); " << minimum(x,a) << endl;    // 3
    cout << "minimum(x,b); " << minimum(x,b) << endl;    // 3.14
}
```

# Function templates

## Use the standard library

```
template <typename T, typename U>
auto
minimum(const T& a, const U& b) -> decltype(a+b);
```

adds the unnecessary requirement that there is an **operator+**.

Better:

```
#include <type_traits>

template <typename T, typename U>
std::common_type<T,U>::type
minimum(const T& a, const U& b);
```

`std::common_type<T,U>::type` is  
*a type that T and U can be implicitly converted to*

# Function templates

min\_element: minimum element in iterator range

```
template<typename FwdIterator>
FwdIterator min_element(FwdIterator first, FwdIterator last)
{
    if(first==last) return last;

    FwdIterator res=first;

    auto it = first;
    while(++it != last){
        if(*it < *res) res = it;
    }
    return res;
```

Use:

```
int a[] {3,5,7,6,8,5,2,4};
auto ma = min_element(begin(a), end(a));
auto ma2 = min_element(a+2,a+4);

vector<int> v{3,5,7,6,8,5,2,4};
auto mv = min_element(v.begin(), v.end());
```

# Function templates

std::min\_element for types that don't have <

Overload with a second template parameter: Compare

```
template<class FwdIt, class Compare>
FwdIt min_element(FwdIt first, FwdIt last, Compare cmp)
{
    if(first==last) return last;

    FwdIt res=first;
    auto it = first;
    while(++it != last){
        if (cmp(*it, *res)) res = it;
    }
    return res;
}
```

Compare must have **operator()** and the types must match, e.g.:

```
class Str_Less_Than {
public:
    bool operator () (const char *s1, const char *s2) {
        return strcmp(s1, s2) < 0;
    }
};
```

## Function templates

`std::min_element` for types that don't have `<`

Example use on list of strings:

```
std::vector<const char *> tl = { "strings", "in", "a", "vector" };

Str_Less_Than lt; // functor

cout << *min_element(tl.begin(), tl.end(), lt);
```

The `Str_Less_Than` object can be created directly in the argument list:

```
cout << *min_element(tl.begin(), tl.end(), Str_Less_Than{});
```

(C++11) lambda: anonymous functor

```
auto cf= [](const char* s, const char* t){return strcmp(s,t)<0;};

cout << *min_element(tl.begin(), tl.end(), cf);
```

# Function objects lambda expressions

## syntax:

```
[capture] (parameters) -> return type {statements}
```

where

`capture` specifies by value (`[=]`) or by reference (`[&]`),  
default or for each named variable (e.g., `[&x, y]`)

`parameters` are like normal function parameter declaration

`return type` can be inferred from `return` statements if  
unambiguous

## Example

```
auto plus = [](int a, int b) {return a + b;}  
  
int x = 10;  
auto plus_x = [=](int a) {return a + x;} // x is captured
```

# Function objects

Predefined function objects: <functional>

## Functions:

```
plus, minus, multiplies, divides, modulus, negate,  
equal_to, not_equal_to, greater, less, greater_equal,  
less_equal, logical_and, logical_or, logical_not
```

## Predefined function object creation

```
operation<type>()
```

E.g.,

```
auto f = std::plus<int>();
```

# Function objects

Example: std::plus from <functional>

## transform with binary function

```
vector<int> v1{1,2,3,4,5};  
vector<int> v2(10,10);  
  
vector<int> res2;  
auto it = std::back_inserter(res2);  
auto f = std::plus<int>();  
std::transform(v1.begin(), v1.end(), v2.begin(), it, f);  
  
print_seq(res2);  
length = 5: [11][12][13][14][15]
```

## Example with accumulate <numeric>

```
auto mul = std::multiplies<int>();  
int prod = std::accumulate(v1.begin(), v1.end(), 1, mul);  
  
cout << "product(v1) = " << prod << endl;  
product(v1) = 120
```

# Function objects

Example: a function object class template

```
template<typename T>
class Less_than {
    const T val;
public:
    Less_than(const T& v) :val{v} {}
    bool operator()(const T& x) {return x < val;}
};

void use_less_than()
{
    auto lt5 = Less_than<int>(5);      // or Less_than<int> lt5{5}
    std::vector<int> v{1, 7, 6, 2, 8, 4, 9, 3};
    std::vector<int> small;

    std::copy_if(begin(v), end(v), std::back_inserter(small), lt5);

    for (auto x : small) {
        cout << x << " ";
    }
    cout << endl;
}
```

## tag dispatch

An option for selecting which version to run is *tag dispatch*

Example: used in std::distance

```
template <class _InputIter>
typename iterator_traits<_InputIter>::difference_type
    distance(_InputIter __first, _InputIter __last, input_iterator_tag)
{
    for (; __first != __last; ++__first) // count hops...
}

template <class _RandIter>
typename iterator_traits<_RandIter>::difference_type
    distance(_RandIter __first, _RandIter __last, random_access_iterator_tag)
{
    return __last - __first;
}

template <class _InputIter>
typename iterator_traits<_InputIter>::difference_type
distance(_InputIter __first, _InputIter __last)
{
    return __distance(__first, __last,
                      typename iterator_traits<_InputIter>::iterator_category());
}
```

# Class templates

- ▶ The container classes `vector`, `deque` and `list` are examples of *parameterized classes* or *class templates*
- ▶ The compiler uses the class template to *instantiate* a class with the given actual parameters
- ▶ No need to manually write a new class for every element type
- ▶ Classes can be parameterized
- ▶ Example: container classes in the standard library
  - ▶ `std::vector`
  - ▶ `std::deque`
  - ▶ `std::list`

*“Container” is a generic concept, independent of the element type*

# Parameterized types

- ▶ Generalize Vector of doubles to Vector of anything.
- ▶ Class template with the element type as template parameter.

Example:

```
template <typename T>
class Vector{
private:
    T* elem;
    int sz;
public:
    explicit Vector(int s);
    ~Vector() {delete[] elem;}

    // copy and move ...

    T& operator[](int i);
    const T& operator[](int i) const;
    int size() const {return sz;}
};
```

# The class template Vector

## Member functions

- Invariant:

- $sz \geq 0$                     (*NB! declared int sz, not unsigned sz*)
- elem pointer to a  $T[sz]$ ;

```
template <typename T>
Vector<T>::Vector(int s){
    if(s < 0) throw invalid_argument("Negative size");
    sz = s;
    elem = new T[sz];
}
template <typename T>
const T& Vector<T>::operator[](int i) const
{
    if(i < 0 || size() <= i) throw range_error("Vector::operator[]");
    return elem[i];
}
template <typename T>
T& Vector<T>::operator[](int i)
{
    const auto& constme = *this;
    return const_cast<T&>(constme[i]);
}
```

# Class templates

## The Container classes

```
class Container {
public:
    virtual int size() const =0;
    virtual int& operator[](int o) =0;    ► generalize on element
    virtual ~Container() {}
    virtual void print() const =0;
};

class Vector :public Container {
public:
    explicit Vector(int l);
    ~Vector();
    int size() const override;
    int& operator[](int i) override;
    virtual void print() const override;
private:
    int *p;
    int sz;
};
```

# Class templates

## Generic Container and Vector

```
template <typename T>
class Container {
public:
    using value_type = T;
    virtual size_t size() const =0;
    virtual T& operator[](size_t o) =0;
    virtual ~Container() {}
    virtual void print() const =0;
};

template <typename T>
class Vector :public Container<T> {
public:
    Vector(size_t l = 0) :elem{new T[l]},sz{l} {}
    ~Vector() {delete[] elem;}
    size_t size() const override {return sz;}
    T& operator[](size_t i) override {return elem[i];}
    virtual void print() const override;
private:
    T *elem;
    size_t sz;
};
```

# The Vector class template

## Constructor with std::initializer\_list

We want to initialize vectors with values:

```
Vector<int> vs{1,3,5,7,9};
```

```
template <typename T>
Vector<T>::Vector(std::initializer_list<T> l)
    :Vector<T>(static_cast<int>(l.size()))
{
    std::copy(l.begin(), l.end(), elem);
}
```

*The pedantic static\_cast<int> is used as  
std::initializer\_list<T>::size() returns an unsigned type*

# Class Templates

## Definition of function members

```
template <typename T>
void Vector<T>::print() const
{
    for(size_t i = 0; i != sz; ++i)
        cout << p[i] << " ";
    cout << endl;
}
```

- ▶ Function members in a class template are function templates
- ▶ `print()` works for all types with an `operator<<`
- ▶ “*Duck typing*”:  
*if it walks like a duck and quacks like a duck, it is a duck*

# Class Templates

## Definition of member functions

```
template <typename T>
void Vector<T>::print() const
{
    for(size_t i = 0; i != sz; ++i)
        cout << p[i] << " ";
    cout << endl;
}

► Works for all types with
operator<<
► but not for elements of
type
struct Foo{
    int x;

    Foo(int d=0) :x{d}{}
};
```

Template specialization for the type Foo:

```
template<> full specialization: no template arguments
void Vector<Foo>::print() const
{
    for(size_t i = 0; i != sz; ++i)
        cout << "Foo("<<p[i].x << ")";
    cout << endl;
}
```

# Template specialization

- ▶ Class Templates can be specialized
  - ▶ fully
  - ▶ partially
- ▶ Function templates can be specialized
  - ▶ fully
  - ▶ *but overloading is always preferable*

# Templates, comments

- ▶ Templates have parameters
  - ▶ type parameters: declared with **class** or **typename**
  - ▶ value parameters: declared as usual, e.g., **int N**
- ▶ The compiler needs the template definition to instantiate  
⇒ it must be in the *header file* (if used by others)
- ▶ Overloading:
  - ▶ Functions can be overloaded ⇒ function templates can be overloaded
  - ▶ Classes cannot be overloaded ⇒ class templates cannot be overloaded
- ▶ Template specialization:
  - ▶ Class templates can be specialized *partially* or *fully*
  - ▶ Function templates can only be *fully* specialized, *but*
    - ▶ Specializations are not overloaded
    - ▶ Often better/clearer to overload with a normal function (not a template) than to specialize

# Template parameters

## Types or values

```
template <typename T, int N>
struct Buffer{
    using value_type = T;
    constexpr int size() {return N;}
    T buf[N];
};
```

- ▶ Buffer: like an array that knows its size
  - ▶ No overhead for heap allocation
  - ▶ Template parameters must be **constexpr**
    - cannot have variable size
  - ▶ cf. std::array
- ▶ The size is included in the type
- ▶ The size as value parameter to the template
- ▶ An alias (value\_type) and a **constexpr** function (size())
  - ▶ Users can access (read) template parameter values

# Template parameters and alias

All standard containers has a “member type“ (nested type name)  
named `value_type`

```
template <typename T>
class Container{
public:
    using value_type = T;
    ...
};

template <typename Cont>           template parameters
typename Cont::value_type&        return type
get_first(Cont& t)                function name and parameters
{
    return *t.begin();
} Here typename is needed by the compiler to know that the name
Cont::value_type is a type before the template is instantiated
void example()
{
    Vector<int> v{2,4,3,5,4,6};
    cout << "first element of v is " << get_first(v) << endl;
}
```

# Alias

**using** can be used to create type aliases

```
using size_t = unsigned int;
```

including templates:

```
using IntVector = Vector<int>;
```

## Classes and polymorphism

References to sections in Lippman

Dynamic polymorphism and inheritance chapter 15 – 15.4

Accessibility and scope 15.5 – 15.6

Type conversions and polymorphism 15.2.3

Inheritance and resource management 15.7

Polymorph types and containers 15.8

Multiple inheritance 18.3

Virtual base classes 18.3.4 – 18.3.5

# Suggested reading

References to sections in Lippman

Customizing algorithms 10.3.1

Lambda expressions 10.3.2 – 10.3.4

Binding arguments 10.3.4

Function objects 14.8

Class templates 16.1.2

Template arguments and deduction 16.2–16.2.2

Type aliases 2.5.1

Trailing return type 16.2.3

Templates and overloading 16.3